



## TM-295 Ticket Printer

*Technical Specification*

The TM-295 Ticket Printer is the world's smallest package slip printer providing durable, reliable performance.

## DESCRIPTION

### Features and benefits

The TM-295 Printer is a terminal ticket printer with the speed and versatility to make it an economical choice for industrial scale applications.

Its versatility is demonstrated by its list of functions. It prints multiple character sizes, has forward and backward paper feed. You can program page length for page sizes from 3.5 inches square to 7 by 10 inches. The TM-295 Printer even has a cash drawer kickout function.

It uses standard RS-232 interface, making it an easy peripheral to apply to data gathering equipment. Its 512 byte memory buffer allows data reception during printing, improving throughput by cutting waiting time from the host device.



## SPECIFICATIONS

**Print method** – 7-pin, shuttle impact dot matrix

**Character matrix** – 5 x 7 or 7 x 7 matrix

**Character spacing** –

5 x 7 font – ANK: 0.63 characters per inch

Graphics – 0.315 characters per inch

7 x 7 font – ANK: 0.63 characters per inch

Graphics – 0.315 characters per inch

**Character height** –

0.11 inch, standard font

Software selectable: Double-wide,

double-high, quadruple

**Line feed spacing**– 0.16 inch

**Print speed** – 1.9 to 2.3 lines per second

**Paper feed speed** –

Approximately 25 lines per second

**Print area** – 2.59" wide

**Print head reliability** – 100 x 10<sup>6</sup> strokes per pin

**Ribbon** –

Cartridge type

Life span: Approximately 1.5 million characters

**Character buffering** – 512 bytes

**DC voltage** –

24 VDC ± 10%, 100 mA idle,

600 mA mean, 5.5A peak

**Interface** – RS-232 serial

**Selectable baud rates** – 1200, 2400, 4800, 9600

**Parity** – none, even, or odd

**Word length** – 7 or 8 data bits,

**Stop bits** – 1 or 2 stop bits

**Handshaking** – Xon, Xoff or DTR/DSR

**Environment** –

Temperature: 41°F to 104°F (5°C to 40°C)

RFI: Moderate tolerance

Dust: Noncorrosive, nonconductive

**Agencies** –

FCC Class A

CE marking

UL (power supply)

CSA (power supply)

**Dimensions** –

7" W x 4" H x 7.5" D

(17.78 cm x 10.16 cm x 19.05 cm)

**Shipping weight** – 4 lb (1.8 kg)

**Power supply** – AC to 24 VDC, weight 3 lb (1.2 kg)

**Avery Weigh-Tronix - USA**

1000 Armstrong Drive,  
Fairmont, MN 56031-1439 USA  
usinfo@awtxglobal.com  
Toll-Free: (800) 533-0456  
Phone: (507) 238-4461

**Avery Weigh-Tronix - UK**

Foundry Lane, Smethwick,  
West Midlands B66 2LP UK  
info@awtxglobal.com  
Phone: +44 (0) 8453 66 77 88  
Fax: +44 (0) 121 224 8183

Please call us or visit [www.averyweigh-tronix.com](http://www.averyweigh-tronix.com)  
for your nearest Avery Weigh-Tronix distributor

# Avery Weigh-Tronix

