



TS Series

Floor Scales

Industrial Duty Low Profile Floor Scales

The right features
The right configurations
The right price



Big Red series floor scales by Triner Scale

- WEATHER PROOF
- QUICK AND EASY SETUP
- DIAMOND PLATE DECK
- STAINLESS STEEL JBOX
- SQUARE & RECTANGULAR SIZES
- POWDER COATED




Top-access leveling adjustment



Precision ball and cup feet minimize side load shocks



Top-access to pre-wired junction box



Built in protection for harsh environments



NTEP approved
COC# 93-074

NEW!

“Big Red”

Series Floor Scale Decks
by Triner Scale

TRINER SCALE

“Accurate Around the World Since 1897”

SPECIFICATIONS

General

- Quick, easy setup
- High accuracy
- Heavy duty steel construction
- Diamond steel deck plate
- Durable powder coated finish
- Height adjustable precision ball & cup leveling feet
- Top access to leveling feet for easy adjustment
- Top access junction box

Technical

- Four premium alloy steel nickel Plated loadcells
- NTEP approved *
- Loadcells are watertight for wet environments
- Loadcell capacity is 2 times the scale capacity
- Built in overload protection
- Nema 4x watertight junction box
- Shipping weight:
 - 4' x 4' = 315 lb
 - 5' X 5' = 450 lb
 - 4' X 6' = 435 lb
 - 4' X 8' = 800 lb
 - 5' X 7' = 905 lb

Dimensions & Capacities

Deck Size	Capacity	Model #
4' x 4' x 4.5" *	5,000 lb	TS5-44
4' x 4' x 4.5" *	10,000 lb	TS10-44
5' x 5' x 4.5" *	5,000 lb	TS5-55
5' x 5' x 4.5" *	10,000 lb	TS10-55
4' x 6' x 4.5" *	5,000 lb	TS5-46
4' x 6' x 4.5" *	10,000 lb	TS10-46
4' x 8' x 4.5"	5,000 lb	TS5-48
4' x 8' x 4.5"	10,000 lb	TS10-48
5' x 7' x 4.5"	5,000 lb	TS5-57
5' x 7' x 4.5"	10,000 lb	TS10-57

Includes

- Pre-wired Junction Box
- 20 ft. Homerun Cable
- Setup Instructions

CONFIGURATIONS

- Deck alone



- Deck with anchor plates and front ramp



- Deck with anchor plates, ramps and indicator stand



OPTIONS

- Ramps
- Anchor Plates
- Floor mount indicator stand

* NTEP
approved

Triner Scale and Manufacturing Company, Inc.
Toll Free: (800) 238-0152
Tel: (662) 890-2385 Fax: (662) 890-2386
www.trinerscale.com